



# LOBASOL<sup>®</sup> Markant

The natural Oil/Wax combination

For impregnation of untreated wood  
and parquet floors

- ▶ BASED ON NATURAL OILS AND WAXES
- ▶ ACCENTUATES THE WOODS  
NATURAL COLOUR AND STRUCTURE
- ▶ WATERPROOF
- ▶ DIRT REPELLENT
- ▶ SCRATCH RESISTANT





# LOBASOL® Markant

## The natural Oil/Wax combination

### GENERAL:

LOBASOL® Markant Natural Hardwax Oil is suitable for the impregnation of solid wood, parquet floors and cork. LOBASOL® Markant provides a durable surface to the floor with a highly elastic protective coat which makes the floor abrasion resistant, water and dirt repellent. The natural colour and texture of the wood will also be accentuated.

### APPLICATION:

The floor must be dry and free of contamination. Shake LOBASOL® Markant well before use, don't apply below +15° C.

### FIRST COAT:

#### European woods:

Apply LOBASOL® Markant Natural Hardwax Oil thinly and evenly using a special brush or roller. Remove excess material with a cloth or rubber squeegee after about 10 minutes (using a machine if possible). Applying one or two coats using a spatula is an alternative method. Attention! Do not use a spatula on irregular absorbing wood types as beech, cherry, maple, etc. Drying time between 12 and 24 hours (depending on the amount of hardwax oil applied and the climatic conditions).

### SECOND COAT:

Apply LOBASOL® Markant Natural Hardwax Oil thinly and evenly using a special brush or roller.

Drying time: 12 to 24 hours per coat, depending on the amount of Hardwax Oil applied and the climatic conditions. After that time the floor is usable. Full hardness is reached after 8 to 14 days. No wet cleaning or floor covering should be attempted until this time. Maintain and clean using LOBA® Parkettoil. Deep clean with LOBA® WaxRemove.



### CONSUMPTION:

Depending on the porosity of the wood and the application method, roller or brush: approx. 80 g/m<sup>2</sup> per coat. Spatula: approx. 20 g/m<sup>2</sup> per coat.

### STORAGE:

In original closed packaging LOBASOL® Markant Natural Hard Wax Oil has a shelf life of approx. 12 months. Store and transport between +5° C and + 25° C.

### ADDITIONAL INFORMATION:

See technical data sheets on [www.lecoluk.com](http://www.lecoluk.com).



**Lecol**  
Postbox 51 NL-5140 AB  
Waalwijk, The Netherlands  
Tel.: 0870 922 2837  
Fax.: +31 416 566 531  
[sales@lecoluk.com](mailto:sales@lecoluk.com)  
[www.lecoluk.com](http://www.lecoluk.com)

