



TECHNICAL DATA SHEET

Swift®therm 3122

Type of Adhesive Hot-melt adhesive.

Product Benefits – long open time

- can be used for lateral bonding in bookbinding field

Typical Applications Labelling on metal boxes.

Suitable substrates Metal, paper.

Typical Properties

Property	Value
Colour	yellow
Softening point (R&B)	approx. 85°C
Viscosity	Brookfield CAP 2000
	approx. 1,800 mPas at 150°C
	approx. 900 mPas at 175°C
	approx. 500 mPas at 200°C
Shelf life	12 months

Last Updated: 10/30/2015





TECHNICAL DATA SHEET

Application Instructions

Application temperature:

pick up: between 140°C and 160°C

Side seam: between 140°C and 170°C, according to the

operating conditions.

Open time / Setting time: long (varies according to the operating

temperature, the weight of adhesive and the substrate).

Cleaning Instructions Plea

Please contact your local Sales Office for available cleaning

solutions.

Typical Packaging Please contact your local Sales Office for available packaging

options.

Storage Conditions In original sealed packaging protected from sun, dust, moisture

and high temperatures. Clean and dry conditions above 15°C

and below 35°C.

Disposal Advice Please refer to the MSDS for disposal instructions.

Safety Advice Please refer to the MSDS for safety advice.

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: The information, specifications, procedures and recommendations herein (together "information") are based on our experience and we believe these to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that the information will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.



NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

H.B. Fuller Company

info-europe@hbfuller.com www.hbfuller.com/ eimea/contact-us