PLASTOCOLL L 1350 Vorstrich

Technical Information

Area of application

PLASTOCOLL L 1350 Vorstrich is an easy-to-apply two-component polyurethane-based precoat for hardening absorbent sole leather and upper leather as well as primering — with the addition of 5 up to 10% Härter — as a protective layer against leather grease and plasticizers.

Technical data

Raw material base:	Polyurethane
Cleaning and thinning:	WAKOL LÖSER 30
Adhesive application:	using a brush or suitable applicator.
Drying time:	WAKOL Härter H: approx. 15 minutes to max. 8 hours WAKOL L 2920 Härter: approx. 15 minutes to max. 3 days
Potlife:	WAKOL Härter H: approx. 24 hours WAKOL L 2920 Härter: approx. 5 days
Storage temperature:	not below + 10°C; susceptible to frost
Storage time:	approx. 12 months in tightly sealed container
Danger classification according to GefStoffV:	refer to MSDS

Instructions for use

The precoat must be completely dry before applying the adhesive.

The temperature of the material, room and adhesive should be between + 15°C and + 25 °C.

Important

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience. The variety of materials used and the different work conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend performing sufficient tests or a pilot run. We gladly provide technical advice.

This Technical Information supersedes all previous versions.

Wakol GmbH
Bottenbacher Straße 30
D-66954
Pirmasens
Tel. +49 6331 8001 131
Fax +49 6331 8001 890
www.wakol.com

Wakol GmbH
Industriestraße 5
A-6841
Mäder
Tel. +43 5523 64 700
Fax +43 5523 64 700 64
www.wakol.at

Wakol Adhesa AG/SA
Stauffacher Straße 130 A
CH-3014
Bern
Tel. +41 31 9210 755
Fax +41 31 9212 968
www.wakoladhesa.ch

Wakol Foreco srl
Via Kennedy 75
I-20010
Marcallo con Casone
Tel. +39 02 9761 939
Fax +39 02 97 253 021
www.wakolforeco.it

Loba-Wakol Polska Sp.z o.o.
ul. Sławęcińska 16, Macierzysz
PL-05-850
Ożarów Mazowiecki
Tel. +48 22 436 24 20
Fax +48 22 436 24 21
www.loba-wakol.pl

Maiburg Lijmen B.V.
Schutweg 6
NL-5145 NP
Waalwijk
Tel. +31 416 566 530
Fax +31 416 566 531
www.maiburg.nl