

## Swift® Hardener 9502

<b>Type of Adhesive</b>	Non-flammable hardener for polyurethane, polychloroprene and nitrile solvent-based adhesives
<b>Product Benefits</b>	Slow-curing hardener
<b>Typical Applications</b>	Shoe industry (adhesion of elements of the shoe: leather, rubber, synthetic materials), conveyor belts (adhesion of rubber)
<b>Suitable substrates</b>	These are indicated on the technical data sheet for the adhesive with which the hardener is used.

### Typical Properties

Property	Value
Base	Isocyanate
Colour	dark brown liquid
Dry extract	around 30%
Density at 20°C	approx. 1.290 g/cm <sup>3</sup>
Isocyanate percentage	8 to 9%
Shelf life	12 months

<b>Application Instructions</b>	The mixing ratio, the life cycle in containers and the open time are indicated on the technical data sheet of the adhesive with which the hardener is used.
<b>Cleaning Instructions</b>	Please contact your local Sales Office for available cleaning solutions.
<b>Typical Packaging</b>	Please contact your local Sales Office for available packaging options.
<b>Storage Conditions</b>	Store in a clean and dry place above +10°C and below +30°C. Crystal formation at temperatures below +10°C. This product is sensitive to ambient air humidity. It is therefore important to keep the packaging hermetically sealed. Reseal the packaging and store it in a dry place.
<b>Disposal Advice</b>	Please refer to the MSDS for disposal instructions.
<b>Safety Advice</b>	Please refer to the MSDS for safety advice.